



- Cures in seconds through UV-blocked plastics
- Faster than hot-melt and low capital costs
- Low outgassing and no condensation
- Structural strength to plastics, glass, and metal
- Small manufacturing footprint
- Reduced labor
- One-part adhesives
- No two-part mixing or waste
- No two-part racking, stacking, and waiting
- · Easy to dispense and clean
- In-line inspection
- Solvent free
- Silicone free
- RoHS Compliant

Adhesives for Vehicle Lighting Assembly

An early innovator in the use of UV light-curable adhesives for head lamp assembly, Dymax has been providing tier one automotive manufacturers of vehicle lighting with adhesives and sealants for over 30 years. New advances in adhesive technologies provide additional application opportunities for manufacturers of vehicle lighting to dramatically lower production costs. Solvent-free adhesives for headlamp assembly cure in seconds and provide in-line cure for immediate quality control inspection. They resist harsh environments and withstand high temperatures to form strong structural bonds to glass, metal, plastic, and difficultto-bond-to substrates. High-strength gap filling allows for smaller bond areas and larger reflective surfaces for brighter headlamps. Dymax adhesives are ideal for bonding lenses to reflector housings and vent-hole sealing, as well as sealing LED light assemblies.



Plastic Head Lamp Assembly

Product	Features	Applications	Viscosity, cP	Durometer Hardness
3069	UV/visible light cure; flexible plastic bonder; thermal shock resistance	Sealing LED assemblies; potting; lens bonding; LED assemblies	450	D55
3099	UV/visible light cure; moisture resistant; fast cure; plastic bonder	Bonding lens to reflector; potting; LED assemblies	150	D75
6-621	Multi-Cure® (heat or activator cure) for shadowed areas; bonds metal, glass, and plastic	Ruggedizing and sealing vacuum ports	800	D80
846-GEL	Structural strength bonds	Lead tacking and sealing	30,000	N/A
GA-105	UV/visible light cure; form-in- place/cure-in-place gasket; moisture resistant; soft; flexible; low compression set	Headlamp, tail light, and LED sealing	40,000	00-70

Recommended Light-Curing Systems

Successful light-curing processing demands that the curing equipment be matched to the resin to achieve optimum performance and cost savings. Dymax manufactures light-curable materials and curing systems, and specializes in creating the best light-curing processes for individual applications. Our technical specialists are ready to help you maximize your profits and improve product performance.



.....

www.dymax.com

Americas USA | +1.860.482.1010 | info@dymax.com

Europe Germany | +49 611.962.7900 | info_de@dymax.com Ireland | +353 21.237.3016 | info_ie@dymax.com

Asia

Singapore | +65.67522887 | info_ap@dymax.com China | +86.755.83485759 | dymaxasia@dymax.com Hong Kong | +852.2460.7038 | dymaxasia@dymax.com Korea | +82.31.608.3434 | info_kr@dymax.com

©1998-2020 Dymax Corporation. All rights reserved. All trademarks in this guide, except where noted, are the property of, or used under license by, Dymax Corporation, USA.

Technical data provided is of a general nature and is based on laboratory test conditions. Dymax does not warrant the data contained in this bulletin. Any warranty applicable to the product, its application and use is strictly limited to that contained in Dymax standard Conditions of Sale published on our website. Dymax does not assume responsibility for test or performance results obtained by users. It is the user's responsibility to determine the suitability for the product application and purposes and the suitability for use in the user's intended and methods. The user should adopt such precautions and use guidelines as may be reasonably advisable or necessary for the protection of property and persons. Nothing in this communication shall act as a representation that the product use or application will not infringe on a patent owned by someone other than Dymax or at as agrant of license under any Dymax Corporation Patent. Dymax recommends that each user adequately test its proposed use and application before actual repetitive use, using the data in this communication. As a general suitability of the product application before actual repetitive use, using the data in this communication.